



YACIMIENTOS PETROLIFEROS FISCALES BOLIVIANOS
GERENCIA DE REDES DE GAS Y DUCTOS
DISTRITO REDES DE GAS SANTA CRUZ.

ANEXO 4

PLANOS

HOJA:
2 DE 5

PLANILLA DE FIERROS												
ACERO				DOBLADO								COMENTARIOS
CODIGO	No. PIEZAS	DIÁMETRO	LONG.	TIPO	A	B	C	D	E	F	G	
101	16	8 mm (5/16")	8200	4	300	1900	1900	1900	1900	300		
102	32	8 mm (5/16")	2460	3	300	1860	300					
103	32	8 mm (5/16")	2460	3	300	1860	300					
104	13	10 mm (3/8")	6580	3	2350	1880	2350					
105	13	10 mm (3/8")	6580	3	2350	1880	2350					
106	26	10 mm (3/8")	2750	6	100	2350	300					
107	26	10 mm (3/8")	2750	6	100	2350	300					
108	13	10 mm (3/8")	2060	3	100	1860	100					
109	13	10 mm (3/8")	2060	3	100	1860	100					

LISTA DE MATERIALES DE TAPA METALICA				
CÓD.	DESCRIPCIÓN	LONGITUD	CANTIDAD	TOTAL
1	PLANCHAS ANTIDESLIZANTES (PL 1610x1610x3 mm)	-	-	2.59 m2
2	PERFIL L 2x2x3/16" (L 50 x 50 x 5 mm) BASE	1610	4	4040 mm
3	PLETINA DE ACERO ASTM A36 2" x 3/16" TAPA	2265	2	4530 mm
4	JALADOR DE FIERRO LISO Ø 1/2" (13 mm) CON SEGURO PARA CANDADO	400	1	400 mm
5	FIERRO CORRUGADO Ø 3/4"	-	-	8500 mm
6	TUBO DE VENTILACIÓN Ø 2"	750	1	1750 mm